Tender documents charges Rs: 2,000/-(non refundable/nontransferable)

GOVERNMENT OF SINDH INSPECTORATE OF MINES MINES & MINERAL DEVELOPMENT DEPARTMENT

Tender documents charges receipt No	Tender Documents No: CIM/ADP 13-14/RS&ODDC/Tender/M&E/2014/
	TO,
FROM: CHIEF INSPECTOR OF MINES	M/S
GOVERNMENT OF SINDH ST: 19/1, BLOCK-6, GULSHANE IQBAL, NIPA, CHORANGI, KARACHI.	
Invitation to tender No. Website Display vide & Newspaper Publication vide No. INF-KRY-purchase of stores for the Inspectorate of Mines,	NO: 439/2014 Dated 14.02.2014 for the
TENDER FOR THE SUPPLY	OF STORES
Date of submission of tender: on or before: 13.03.2014 up	to 12.30 P.M
Date of opening of tender: 13.03.2014 at 03.00 P.M	
Venue of tender opening: -	Office of Chief Inspector of Mines, Mines & Mineral Development Department, Government of Sindh St:19/1, Block-6, Gulshan-e-Iqbal, Near NIPA, Karachi
TOTAL COST OF BID	••••••

Dear Sir.

- 1. You are hereby invited to submit your tender for the supply of stores as detailed in the schedule to the invitation to tender subject to the conditions mentioned here under and given in the schedule. The tenderers quoting against this invitation to tender shall be deemed to have read and understood the conditions thereof.
- 2. The tenderers shall quote the bids on the PRESCRIBED TENDER FORM,(Annexure-A) schedule to the invitation to tender, on the basis indicated therein for the delivery of stores at consignee's end basis at Lakhra District Jamshoro and shall sign the certificate given therein to the effect that the store shall be supplied exactly, in accordance with the requirements as specified in this schedule. In case there is any deviation, it should be clearly stated by the tenderer in tender form otherwise it will be presumed, that offer is strictly in accordance with the requirement and specifications. Tender with separate attachment for specification shall not be entertained.
- 3. Tender should be accompanied by bid security equal to 2% (two percent) value of their bid price i.e grand total of total cost instead of grand total of total unit cost, in the shape of pay order/ demand draft from any scheduled bank in name of "Chief Inspector of Mines, Sindh Karachi" and shall be attached with the tender, without which no tender will be accepted.
- 4. Bid security shall be released to the unsuccessful bidders once the contract has been signed with the successful bidder or the validity period has expired.
- 5. The quantity mentioned against any item in the schedule inviting tender can be increased or decreased at the time of the award of contract.
- 6. The successful tenderer shall have to ensure the supply of the stores upto **04.06.2014** failing which the tender shall be cancelled and the security deposit shall be forfeited.
- 7. Original receipt in token of having purchased the tender form must be enclosed with the tender.
- 8. Tenderers shall submit attested photocopy of the National Tax Number Certificate from the Income Tax Department for the year 2013-14.

- 9. The inspection of stores will be carried out by the consignee or any committee constituted by Government in this behalf, in the premises of the office of the Chief Inspector of Mines, Sindh, ST:19/1, Block-6, Gulshan-e-Iqbal, Near N.I.P.A, Chowrangi, Karachi.
- 10. Failure to submit the tender in the manner prescribed in this invitation to tender will be rendered the same to be ignored / rejected.
- 11. The purchase does not pledge to accept the lowest or any tender & the purchaser reserves the right to reject or accept any tender or tenders in full or in part or reject all the tenders without assigning any reasons thereof.
- 12. Model number and make may be enclosed along with the relevant literature/ catalogue / brochures.
- 13. The bidder shall fill the sales tax coloums of tender form with sales tax at existing % age.
- 14. The bidder shall furnish the H.S Code against each and every imported item.
- 15. The successful tenderers will be bound to make delivery after carrying-out the inspection for respective places as mentioned at Serial No.09.
- 16. After coming into force of the procurement contracts, dispute, between the parties to the contract shall be settled by arbitration as per rule.
- 17. Income Tax at existing rate including existing surcharge shall be deducted at source. If there is any dispute with regard to income tax the supplier may submit the refund claim to CBR as per rule.
- 18. 20% of sales tax amount mentioned in the S.T column of tender documents shall be deducted at source while making payment to supplier (successful bidder) and the supplier (successful bidder) has to furnish S.T invoice of remaining S.T amount, i.e 80% of S.T amount.
- 19. Supplier (successful bidder) has to pay award fee at the rate of 0.25% of the award.
- 20. Supplier (successful bidder) has to pay stamp duty @ 0.2% of the award at the time of execution of Procurement Contract.
- 21. Any other tax/duty applicable at the time of payment against the supply of stores shall be deducted source.

- 22. The supplier (successful bidder) shall be required to furnish the attested copy of import documents along with the bills.
- 23. Successful bidders to whom offers for the supply of stores shall be issued, shall have to provide 5% performance security of the amount of contract prices/offer prices, in the form of pay order or demand draft or bank guarantee. The validity of performance security shall extend at least ninety days beyond the date of completion of contract.
- 24. The supplier has to provide training in operating the equipment as and when required by the purchaser.
- 25. All conditions pertaining to purchase of stores mentioned in Sindh Public Procurement Rules 2010 including any amendment made so far shall be applicable.

(MUHAMMAD KHALID MIRZA) CHIEF INSPECTOR OF MINES, SINDH, KARACHI

Annexure-A TENDER FORM

GOVERNMENT OF SINDH INSPECTORATE OF MINES MINES & MINERAL DEVELOPMENT DEPARTMENT

Schedule to invitation to tender no: - Website Display vide www.pprasindh.gov.pk

on 10.02.2014 & Newspaper Publication

vide No INF-KRY: NO: 439/2014 Dated

14.02.2014

Date of receipt of tender: - on or before 13.03.2014 upto 12.30 P.M

Date & time of opening of tender: - 13.03.2014 at 03.00 P.M

Venue of tender opening:-

Office of the Chief Inspector of Mines, Mines & Mineral Development Department, Government of Sindh, St:19/1, Block-6, Gulshan-e-Iqbal, Near NIPA, Karachi.

Offer shall remain open for 90 days from the date of opening of tender. The tenderers shall quote on free delivery installation and demonstration basis to the consignee at F.O.R to Mine Rescue Station & Occupational Disease Detection Centre at Lakhra Near Lakhra Police Station, District Jamshoro.

The successful tenderer shall have to ensure the supply of the stores upto **04.06.2014**.

Sealed tenders will be received and opened in the office of the Chief Inspector of Mines, Mines & Mineral Development Department, Government of Sindh, St:19/1, Block-6, Gulshan-e-Iqbal, Near NIPA, Karachi on the date and time mentioned above.

S R · N O	STORES	SPECIFICATION/DRAWING NO AND OTHER PARTICULARS TO GUIDE SUPPLY.	QUANTITY	UN IT	ST PEF	R UNIT TOTAL	TOTAL COST
1	Accessories/Spares for Breathing Apparatus (Drager PSS BG-4		50				

	Plus (EP). Oxygen-Cylinder 2L / 200 bar (steel) with G 3/4" connection.				
2	Accessories for testing unit (Test It-6100) used for testing Breathing Apparatus (Drager PSS BG-4 Plus (EP). a) Test Set. b) Fill Station. c) Dust Fitter Pads		50 50 200		
3	Multi Gas Monitor CH4,CO,H2S,CO2,	(Mini warm) for simultaneous five gases to detect i.e CO ₂ , CO, O ₂ ,H ₂ S,CH ₄ , for 8 hours operating period at 25°c with infrared sensor, alarm and data logging along with standard accessories. Made in EU, USA, Japan or Similar.	02		
4	Multigas Detector (bellow type)	Made in EU, USA, Japan or Similar.	04		
i.	Multigas detector tubes for item NO.4	Made in EU, USA, Japan or Similar.			
	a) CO2.		10 Pkts 10		
	b) CO. c) H2S.		Pkts 10 Pkts		
	d) NO2.		10 Pkts 10		
	e) CH4.		Pkts		
5	Pocket Digital Methanometer for measuring methane gas in mines.	Digital, Pocket size with Data logging hours = 78 hours or without data logging facility. Operating Range = 0 - 100% Resolution 1%. Made in EU, USA, Japan or Similar.	04		
6	Oxygen Monitor Digital for measuring Oxygen in mines.	i) Oxygen measurement 0-25 vol % resolution 0.1 vol % Electrochemical. ii) Temperature -25 ⁰ C - 55 ⁰ C iii) Humidity 10 Up to 90% r.h	04		

		iv) Pressure 700 to 1300 h Pa v) Operation time > 12 Hours vi) Alarming Default 19 vol % - 23 vol % Along with following accessories Charging accessories, Data logging Extension Hoses & Probes, Calibration Adaptor or Carrying Case. Made in EU, USA, Japan or Similar.			
7	CO Monitor Digital for measuring carbon monoxide in mines.	i)Measuring range 0- 500 PPM ii)Alarm threshold 30-60 PPM Temperature – 30 to 50 ⁰ C iii) Humidity 10 Up to 90% r.h vi)Pressure 700 to 1300 h Pa with following accessories connecting cradle, Complete with USB, Dust & water filter & Lather carrying case. Made in EU, USA, Japan or Similar.	02		
8	Multigas Detector (Digital) for measuring gases in mines.	To detect simultaneously 4-5 gases Gas Operating Range of Sensors O2 0-25 Vol, -% CO 0-500 ppm H2S 0-100 ppm CH4 0-100 Vol. % For 8 hours operating period at 25 C with alarm and pump operating with one catalytic CAT EX-Sensor and other three electro chemical (EC) sensors with infrared sensor port for communication with computer, Data longing facility along with standard accessories. Made in EU, USA, Japan or Similar.	02		
9	Flame Proof Auxiliary Ventilation Fan 18 dia,1500 rpmL50 cycle, 440 v, 5000 cft.	18" Dia 1500 RPM 50 cycle 440V, 5000 cft Made in EU, USA, Japan or Similar.	01		

10	Folding Ventilation Tubes Venial 18" dia.	Made of Vinyl. 18" Dia with coupling to joint 18" dia tubing.	200 Meter		
		Made in EU, USA, Japan or Similar.	200 1		
11	Portable Generator 63 KVA, 3 Phase, 50 cycle, 440 v.	Powered with water cooled diesel engine with alternator of 60 KVA, 3 Phase 50 Hertz, 440/220 volts with control panel and tool kit. - Electric starting system with maintenance free lead acid battery. - Tropicalized Radiator - Alternator Battery Charger - Heavy Duty Exhaust Silencer - Circuit Bracket - Heavy Duty Fabricated Steel base Frame with anti-vibration mounts - Hours run counter - of/run crank key switch - Protection Devise with indicators for high engine temperature and low oil pressure -Made in EU, USA, Japan or Similar.	02		
12	Portable Generator 22 KVA, 3 Phase, 50 cycle, 440 v.	Powered with water cooled diesel engine with alternator of 40 KVA, 3 Phase 50 Hertz, 440/220 volts with control panel and tool kit. - Electric starting system with maintenance free lead acid battery. - Tropicalized Radiator - Alternator Battery Charger - Heavy Duty Exhaust Silencer - Circuit Bracket - Heavy Duty Fabricated Steel base Frame with anti-vibration mounts - Hours run counter - of/run crank key switch - Protection Devise with indicators for high engine temperature and low oil pressure -Made in EU, USA, Japan or Similar.	01		

13	Oxygen Boost An Oxygen Pump to dec from storage into apparatus Technical Dat	Transfer ant oxygen e cylinders cylinders. a;	Electric Driven, Nominal pressure PN200 bar/300 bar (2900/4350 psi). Max. pressure 220 bar/330 bar (3190/4785 psi) Power supply 400 V/50 Hz, optional 60 Hz. Control voltage 24 V AC Power-supply plug CEE 16 A. Drive 1.1 kW, 230 V/400 V. Pump Single-stage, 2-cylinders. Charging connection 4 x PN 200, G3/4" DIN. Made in EU, USA, Japan or Similar.	01 Complete Unit		
	Nominal Pressure:	PN200bar (2900 psi)				
	Max Pressure:	220 bar (3190 psi)				
	Power Supply:	400 V/50 Hz, optional 60 Hz.				
	Control Voltage	24 V AC.				
	Power Supply Plug.	CEE 16 A				
	■ Drive.	1.1 KW, 230 V/400 V				
	■ Pump	Single – stage, 2-cylenders				
	Charging Connect ion	4x pn 200, G ³ / ₄ "				
	Dimensi on Approx.	680 x 580 x 1100 mm (L x W x H)				
	Weight Approx: Drager or Similar, EU/Japan/ USA Made.	128 kg (58 lbs.)				

i	Oxygen Cylinder, 50 L 200 bar, Valve connection G3/4 PIN 477.	04		
ii	Cylinder Holder,	04		
iii	High Pressure Hose Connecting hose between n.p. 200 supply cylinder and transfer pump, max. working pressure 220 bars, length 1.5 m. Transfer pump connecting side:	02		
	Transfer R 3/4" pump female cap connecting screw side: R 3/4" Supply female Cylinder manual connecting: connection.			
iv	Charging Hose, Connecting hose between PN 200 charging connection and large apparatus cylinder: max. Working pressure 220 bar 1.5 m long hanging end: G 3/4" male, apparatus cylinder; connection end: G 3/4" female, manual connection.	04		
v	Oxygen Drying cartage, For Booster pumps.	02		
vi	Spare Parts set, For Booster DOB 200/300.	02		
vii	Bushes.	02		

	T = 1000 (0.50		1		
14	Oxylog 1000 (C.U)	i) Time-cycled, volume constant			
	Time-cycled volume	and portable.			
	constant and portable	ii) Optical and audible alarm for			
	emergency ventilator.				
	Optical and audible alarm	paw low.			
	for Paw low (disconnect),	Made in EU, USA, Japan or			
	Paw high (stanosis) and	Similar			
	supply pressure low.		it.		
	Compact, portable		Ü		
	emergency system		ete		
	consisting of;		ld ld		
	Oxylog 1000 Basic		02 Complete Unit		
	Unit				
	 Ventilation Hose 1.5 		00		
	m				
	 Respiratory Valve 				
	Note: DIN 13252 02-gas				
	inlet connection is				
	required.				
	Drager or Similar,				
	EU/Japan/USA, made.				
i	Carrying System 1000		02		
	Carrying system 1000 for				
	Oxylog 1000; Special bag				
	for the transport of				
	Oxylog 1000 and				
	necessary accessories.				
	Optimized for 2 Liter				
	GFK cylinder (B 10208).				
ii	Oxygen Connecting		02		
	Hose 0.5 m				
	02-connecting hose 0.5 m;				
	to connect the pressure				
	reducer and distributor				
	oxyplate; for carrying				
	system 1000 and 2000.				
iii	Distributor Oxyplate		02		
	Distributor to connect the				
	Oxylog 1000/ Oxylog				
	2000 with an oxygen				
	cylinder or with a central				
	gas supply.		6.5		
iv	Revers. Hose 02, DIN		02		
	coupl. 1.5m				
	Reversible hose 02/Air-				
	Reversible hose for				
	distributor connector,				
	quick-release Walther				
	coupling. Alduk 1 02-Pressure		02		
V	Alduk 1 02-Pressure Reducer PI		02		
	Single-Stage compact				
	small pressure reducer for				
	emergency medicine to				
	reduce high-pressure				
1	oxygen from cylinders to				
	L OVUGAN Trom outindors to				

	41		1		
	the required operating pressure. 2 outlets of 4.5				
	bar (non-return safety				
	valve) 1 outlet 02				
	connector; adjustable				
	between 0-15 1/min.				
	Connection PIN Index				
15	VHF Radio Base Station	100 Channel	02		
	with complete	Output 45-65 watts			
	accessories.	Frequency 137-174			
		MHz			
		Busy Channel Lockout			
		DOT, CTCSS and DC Dual Watch			
		Scane, Monitor, Home & Priority			
		Channel with accessories:			
		First Microphone			
		Base Antenna with 100 feet			
		Coaxial cable			
		Heavy Duty Power Supply			
		G.I.Pipe 40 feet with mounting			
		hardware.			
16	Underground	Made in EU, USA, Japan or Similar.	0.1		
10	Communication	Intrinsically safe a set of two Self	01		
	(Intercom) with 300-	powered telephone set along with	Unit		
	meter cable.	sturdy double plastic covered			
		telephone cable.			
		Made in EU, USA, Japan or			
		Similar.			
17	HF Radio Telephone inter	HF Base Station			
	connector complete with	Coverage RX 30KHz-30.000MHz	02		
	Base Station including	in 10 Hz steps, Tx 1,600-30.000	02		
	complete Accessories.	MHz.			
		Power Output: 125/100 Watts, all			
		•			
		moder operation SSB/LSB, AM,			
		CW, including accessories.			
		- Fist Microphone			
		- SP-500 AC Power Supply			
		220VAC, 35 Amp.			
		- 30 MHz Broad Band Antenna			
		with to meters cable RG-213 with			
		connectors			
		- Telegraphic (Morse) Key.			
		- Pipe Mast for Antenna-D.1 Pipe			
		2" dia 40-ft guys 3/16') G.I.Solid			
		<u> </u>			
		wire at Mid and Top positions, Bas			
		e Plate, Anchore and mounting			
		hardware.			
		Made in EU, USA, Japan or Similar.			

18	Oil Safety Lamp (Imported)	- For checking of fire damp and black damp. The fuel container is packed tightly, cotton wool for absorption of sprit. Inner and outer gauzes of 28 inch with leading rings washer and glass Made in EU, USA, Japan or similar.	01		
19	Electric Safety Lamps (Acids).	0-1 amperes, 8-11 oh, capacity 4-6 volt with double filament Made in EU, USA or Japan or similar.	50		
20	Lamp Charger 51 type	For charging 51 lamps at a time along with volt meter and power supply of 220 volt, 50 MHz3 Made in EU, USA or similar.	01		
21	Rock Cutters (Pneumatic)	Medium weight Pneumatic Breakers a) Weight of Breakers = 20 Kgs b) Air Requirement = 26 L/S/6 bar c) Drill Steel Chuck = 25x108 mm d) Hose Connection = 20 mm e) Impact Frequency = 1470 Blows Per minute Accessories: Lubricator, 5 Nos. Narrow Chisel Steel with length of 38 cm Made in EU, USA, Japan or Similar.	02		
22	Safety Helmets of fiberglass. Spotter calibration Test	back cable hook and with chain strap. Made in EU, USA, Japan or Similar.	50		
	Kit.	With complete standard accessories and spares for two years. Made in EU, USA, Japan or Similar.	02		
24	Infra red Imager/Camera for heat and spontaneous composition.	 - Detector Chip a-Si Sensor - Resolution 160 x 120 Pixel - Spectral Range 7-14 mm - Picture frequency 50 Hz - Operating Temperature (-40 C to 85 C) 	01		

		- Temperature Measurement with digital temperature display (1000C°) with report generator, thermal imaging, recorder, trigger and measurement software and other accessories. Made in EU, USA, Japan or Similar			
25	First Aid Training Kit	Stretcher, all types of Bandages and other accessories needful for First Aid Saint John Ambulance Training. Made in EU, USA, Japan or Similar.	05		
26	Fire Supression Foam Generator with spares hoses etc.	Capacity 30G Duration 5 Minute Flow Range 20 Meter working pressure 8 Bar Compressed Air Cylinder 200 Bar. Made in EU, USA, Japan or Similar along with 400 Liters foam in 20 Liter packing. Made in EU, USA, Japan or Similar.	01		
27	Fire Extinguisher	7 1			
i	164g size.	i. For Dry powder Fire Extinguisher. Capacity 9 kg fire rating 43A 233B, working pressure 15 Bar range of discharge 6-8m duration 24 sec. ii. For Foam Fire Extinguisher. Capacity 9L fire rating 21A 183B, working pressure 14 bar range of discharge 8-9m duration 30 sec. Made in EU, USA, Japan or Similar.	10		
ii	124g size	For water Fire Extinguisher. i. Capacity 9L, working pressure 14 Bar range of discharge 9m duration 20 sec. Made in EU, USA, Japan or Similar.	05		
28	Recording Resusci Anne	Plastic model with arrangement or resuscitation and primitive mechanism for training to rescue work in resuscitation of victims Manufactured by Laerdal, Norway or similar.	01		

29	Dust Respirator Picco-20 idle dust respiratory Drager or Similar, EU/Japan/USA, made.	i) Filter system Replaceable plug in filter ii) Duration of use Depends on particle exposure up to several days. iii) Weight Approx. 100g vi) Approval EN 1827 FMP2/FMP3 EN 143 P2/P3 Niosh	10		
		CFR 42 P100/R95 v) Inhalation resistance (30 L/min)			
		< 0.25 mbar			
		iv) Exhalation resistance/repair.			
		With necessary pare parts.			
		Made in EU, USA, Japan or Similar.			
30	Filters for Dust	For item No. 29.	20		
	Respirator.		pkts		
31	Explosimeter (Warnex) with Charging device and	i) Ex-measurement.	05		
	test probe and adopter	0 to 100% LEL,			
	Drager or similar,	Resolution 1% LEL,			
	EU/Japan/USA, made.	0 to 99 Vol% CH4			
		Resolution 0.1 Vol% (0 to 5 Vol%)			
		Resolution 1 Vol% (0 to 99 Vol%) ii) Oxygen measurement.			
		0 to 25 Vol%			
		Resolution 0.1 Vol%			
		Heat reaction and thermal			
		conductivity electrochemical.			
		Temperature			
		-25 to 55 °C-15 to 130 °F			
		Humidity			
		10 up to 99% r.h.			
		Intermittently to 95% r.h.			
		Non condensing			
		Pressure			
		700 to 1300 hPa; 20.7 to 38.4" Hg			
		Operation time			
		> 12 hours			
		Visual, audible and vibrating			
		alarm. Along with following accessories: Charging Accessories,			
		Data Logging, Extension Hoses			
		and Probe, Calibration Adopter,			
		Carrying Case.			
		Made in EU, USA, Japan or			
		Similar.			

32	Pocket weather tracker	Wind Speed	05			
	with following	0.4 to 40.0 m/s	03			
	calliberation.	Air Flow				
	i) Altitude					
	ii) Pressure Trend	0 to 99.999 cfm				
	iii) Barometric pressure.	Temperature				
	iv) Relative Humidity.	-20.0 to 158.0 ⁰ F				
	v) Heat Stress Index.	relative Humidity				
	vi) Dew point.	5.0 to 95.0 % non-condensing				
	vii) Wet bulb temperature	Pressure				
	viii) Density Altitude. ix) Wind Chill	-At 77.0° F < 19.700 ft				
	x). Air Temperature	Altitude				
	xi)Water Temperature.	-At 77.0° F < 19.700 ft Max error +/- 98 ft				
	xii). Wind Speed.	wind Chill				
	, 1					
		1.8 to 89.0 mph,, -50 to 50.0 ⁰ F				
		Heat Index				
		77.0 to 130.0 °F, 0 to 100% RH				
		Dew Point				
		-20.0 to 158.0 °F, 20.0 to 95.0% RH				
		Wet Bulb Temperature				
		32.0 to 100.0 °F, 5.0 to 95.0% RH				
		Density Altitude				
		32.0 to 100.0 °F, 5.0 to 95.0% RH				
		Made in EU, USA, Japan or				
		Similar.				
33	Moving Belt Treadmill,		0.1			
33	Model TM-400, Made in	Speed-18 kph, elevation 0-10%	01			
	Taiwan or similar.	incline, running surface 20"x55",				
	Tur want or brinning	LED Display Speed, time,				
		distance, calories, incline, pulse.				
		Made in EU, USA, Japan or				
		Similar.				
34	B.P Apparatus	Mercurial, bigger desk type	05			
		Made in EU, USA, Japan or Similar.				
35	Weight Machine	Metallic	04			
		Made in EU, USA, Japan or Similar.	0-1			
36	Medical Examination	6ftx2ft made of iron pipe with	02			
	Table		02			
		foam cushion covered with regzene				
		Made in EU, USA, Japan or				
		Similar.				
37	Medical Examination	Stand with bulb with reflective	02			
	Light	benefits				
		Made in EU, USA, Japan or				
		Similar.				
38	Steel Stool	Stain less steel top, Height 18" Dia	05			
		Meter 15"				
		Made in EU, USA, Japan or				
		Similar.				
1					1	

39	Stethoscope	Dual Head Made in EU, USA, Japan or Similar.	05		
40	ENT General Examination Test Kit	Tongue Depressor, Ear Speculum & Nose Speculum (different sizes), Auto Scope, Head Light, Thermometer, Torch. Made in EU, USA, Japan or Similar.	02		
41	Height Scale	Made in EU, USA, Japan or Similar.	02		
42	Sterilizer	Stain less steel Made in EU, USA, Japan or Similar.	05		
43	X-Ray Eliminator	Dual, Made in EU, USA, Japan or Similar.	02		
44	A/B-Scan Verification Ultrasonic Thickness/ Corrosion Meter	 i) Measures range 0.63 mm - 254 mm in 1-E mode ii) Resolution of 2.54 - 102 mm in E-E mode (through paint iii) Stability indicator, bar graph for visual cursors for reading conformation. iv) Stores 64 users definable setups for calibration. Made in EU, USA, Japan or Similar. 	01		
45	Table for officers	Table for officers (6x3 ½) with three drawers along with lock and keys (Panel) with 5 mm tinted Glass or covered with regzine top quality finish.	05		
46	Table for officials	Table for officials (5'x3') with three drawers along with lock and keys in texture lamination wood (Lasani / sony).	10		
47	Chairs	Chairs. (Set a bin Cane) made of seasoned Shisham.	200		
48	Revolving Chair	Revolving Chair (Set a Bin Can), hydraulic seat and back with tilting provision, made of seasoned Shisham.	05		
49	Sofa Set	Sofa Set (Five seators) with ten years foam warranty. Cushion in regzine.	06		

50	Easy Chair with table	Set of 04 Easy Chair with table full	03						
	(4 Chair Table)	Shisham. Chairs (Set a Bin Can).							
51	Almirah Steel	Size (4'x6') Made of SWG 22 MS	50						
		Sheet Four Shelves five							
		compartments with lock & keys.							
		Finish = Grey Colour Hammer							
		Spray painted.							
52	Almirah (Wooden)	Almirah (Wooden) Double Door,	04						
		Size (4'x6'), (Lasani Board).	Size (4'x6'), (Lasani Board).						
53	Bench wooden	Bench wooden for office (5') made	12						
		of seasoned Shisham.							
54	Desks for Training of	10							
	Students	made of seasoned Shisham.							
55	Towel Stands	Towel Stands	20						
56	Split A.C 1.5 Ton	Split A.C 1.5 Ton	08						
		(Japan Made or similar)							
57	Computer P-IV	Computer P-IV Complete with	02						
	Complete with	Printer and scanner branded							
	Printer and scanner,	Core i 3, Ram 4 GB, Hard Disk							
	branded	500 GB, DVD RW, LED 18.5"							

Note: -

Pa	v ordei	· in	favor	of	Chief	Inspector	of	Mines.	Sindh	Karachi	bearing
No	•					•					· ·
2% (two p	ercent)	of to	tal bid	valu	e is end	closed.					
							Sig	nature o	f Owner	rs / Propri	etor
							M/	S			
							Re	gistratio	n No. (if	any)	
							Sta	mp / Sea	al		